Firma: Dynamic Computers DOO
Adresa: Svetosavska 6
Telefon: 063/111-50-29
Fax:
PIB: 112696754
E-mail: prodaja@dynamic-computers.rs

MB AM5 ASRock B650M-HDV/M.2

Šifra: 2491
Kategorija prozivoda: AMD
Proizvođač: AsRock

Cena: 12.947,00 rsd.



CPU
- Supports AMD Socket AM5 Ryzen™ 7000 Series Processors

Memory
- Dual Channel DDR5 Memory Technology
- 2 x DDR5 DIMM Slots
- Supports DDR5 non-ECC, un-buffered memory up to 6400+(OC)
- Max. capacity of system memory: 64GB
- Supports Extreme Memory Profile (XMP) and EXTended Profiles for Overclocking (EXPO) memory modules

Graphics
Integrated AMD RDNA™ 2 graphics (Actual support may vary by CPU)
- 1 x HDMI 2.1 TMDS/FRL 8G Compatible, supports HDR, HDCP 2.3 and max. resolution up to 4K 120Hz
- 1 x DisplayPort 1.4 with DSC (compressed), supports HDCP 2.3 and max. resolution up to 4K 120Hz

LAN
- 2.5 Gigabit LAN 10/100/1000/2500 Mb/s
- Dragon RTL8125BG
- Supports Dragon 2.5G LAN Software
- Smart Auto Adjust Bandwidth Control
- Visual User Friendly UI
- Visual Network Usage Statistics
- Optimized Default Setting for Game, Browser, and Streaming Modes
- User Customized Priority Control

Chipset
- AMD B650

BIOS
- 256Mb AMI UEFI Legal BIOS with GUI support

Audio
- 7.1 CH HD Audio (Realtek ALC897 Audio Codec)
- Nahimic Audio

Slots
CPU:
- 1 x PCIe 4.0 x16 Slot (PCIE1), supports x16 mode*
- 1 x PCIe 4.0 x16 Slot (PCIE3), supports x4 mode*
Chipset:
- 1 x PCIe 4.0 x1 Slot (PCIE2)*
- 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module

- Supports AMD CrossFire™
- 15µ Gold Contact in VGA PCIe Slot (PCIE1)

*Supports NVMe SSD as boot disks

RAID
- Supports RAID 0, RAID 1 and RAID 10 for SATA storage devices
- Supports RAID 0, RAID 1 and RAID 10 for M.2 NVMe storage devices*

*Requires additional M.2 NVMe expansion cards to support RAID 10

Connector
- 1 x SPI TPM Header
- 1 x Power LED and Speaker Header
- 1 x CPU Fan Connector (4-pin)*
- 3 x Chassis/Water Pump Fan Connectors (4-pin) (Smart Fan Speed Control)**
- 1 x 24 pin ATX Power Connector
- 1 x 8 pin 12V Power Connector
- 1 x Front Panel Audio Connector
- 1 x Thunderbolt™ AIC Connector (5-pin) (Supports ASRock Thunderbolt™ 4 AIC Card)
- 2 x USB 2.0 Headers (Support 4 USB 2.0 ports)
- 2 x USB 3.2 Gen1 Headers (Support 4 USB 3.2 Gen1 ports)
- 1 x Front Panel Type C USB 3.2 Gen2 Header

*CPU_FAN1 supports the fan power up to 1A (12W).

**CHA_FAN1~3/WP support the fan power up to 2A (24W).
CHA_FAN1~3/WP can auto detect if 3-pin or 4-pin fan is in use.

Software and UEFI
Software
- ASRock Motherboard Utility (A-Tuning)
- ASRock Dragon 2.5G LAN Software*
UEFI
- ASRock Full HD UEFI
- ASRock Auto Driver Installer
- ASRock Instant Flash

*These utilities can be downloaded from ASRock Live Update & APP Shop.

Form Factor
- Micro ATX Form Factor: 9.6-in x 8.9-in, 24.4 cm x 22.6 cm

Storage
CPU:
- 1 x Blazing M.2 Socket (M2_1, Key M), supports type 2280 PCIe Gen5x4 (128 Gb/s) mode*
Chipset:
- 1 x Hyper M.2 Socket (M2_2, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*
- 4 x SATA3 6.0 Gb/s Connectors

*Supports NVMe SSD as boot disks

USB
- 1 x USB 3.2 Gen2 Type-C (Front)
- 1 x USB 3.2 Gen1 Type-C (Rear)
- 6 x USB 3.2 Gen1 Type-A (2 Rear, 4 Front)
- 8 x USB 2.0 (4 Rear, 4 Front)

*All USB ports support ESD Protection

Rear Panel I/O
- 2 x Antenna Mounting Points
- 1 x HDMI Port
- 1 x DisplayPort 1.4
- 1 x USB 3.2 Gen1 Type-C Port
- 2 x USB 3.2 Gen1 Type-A Ports
- 4 x USB 2.0 Ports
- 1 x RJ-45 LAN Port
- 1 x BIOS Flashback Button
- HD Audio Jacks: Line in / Front Speaker / Microphone

Accessories
- 1 x User Manual
- 2 x SATA Data Cables
- 2 x Screws for M.2 Sockets

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.