


ASUS TUF GAMING B550M-PLUS matična ploča

Šifra: 2781

Kategorija proizvoda: AMD

Proizvođač: Asus

Cena: 14.946,00 rsd.



Tip procesora:	AMD
Podnožje:	AMD® AM4
Čipset:	AMD® B550
Format ploče:	Micro ATX
Podržana memorija:	DDR4
Podržani procesori:	- Treća generacija AMD Ryzen procesora
Memorija:	3rd Gen AMD Ryzen procesori - 4 x DIMM, Max. 128GB, DDR4 4600(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.) Memory Next Generation AMD Ryzen PRO Processors - 4 x DIMM, Max. 128GB, DDR4 4800(O.C.)/4600(O.C.)/4466(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.) MHz Un-buffered Memory - Dual Channel Memory arhitektura - ECC Memory (ECC mode) podrška va
Multi-GPU podrška:	- AMD 2-Way CrossFireX tehnologija
Integrirana grafička karta:	- 1 x DisplayPort 1.2 - 1 x HDMI 2.1(4K@60HZ)
Slotovi za proširenje:	3rd Gen AMD Ryzen Processors - 1 x PCIe 4.0 x16 (x16 mode) AMD B550 Chipset - 1 x PCIe 3.0 x16
Skladište:	Ukupna podrška za 2 x M.2 slota i 4 x SATA 6Gb/s porta 3rd Gen AMD Ryzen procesori: - 1 x M.2 So storage devices podrškom AMD B550 Chipset: - 1 x M.2 soket 3, sa M Key, Type 2242/2260/2280/22 6Gb/s porta, podržava Raid 0, 1, 10
Mrežna karta:	- Realtek RTL8125B 2.5Gb Ethernet - TUF LANGuard
Zvučna karta:	Realtek ALC S1200A 7.1 Surround Sound High Definition Audio CODEC - Podržava: Jack-detection, M playback Audio Feature: - Exclusive DTS Custom for GAMING Headsets. - Optical S/PDIF out port(s) layers - Premium Japanese audio capacitors
USB:	Rear USB Port (Total 8) - 2 x USB 3.2 Gen 2 port(s)(1 x Type-A +1 x USB Type-C) - 4 x USB 3.2 Gen (Total 6) - 2 x USB 3.2 Gen 1 port(s)(2 x Type-A) - 4 x USB 2.0 port(s)(4 x Type-A)
Konektori na zadnjoj strani:	- 1 x PS/2 keyboard/mouse combo port(s) - 1 x DisplayPort - 1 x HDMI - 1 x LAN (2.5G) port(s) - 2 x Gen 1 (blue) Type-A - 2 x USB 2.0 - 1 x Optical S/PDIF out - 5 x Audio jack(s) - 1 x BIOS FlashBack B
Interni konektori:	- 1 x CPU Fan connector(s) - 1 x CPU OPT Fan connector(s) - 2 x Chassis Fan connector(s) - 2 x Aura Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s) - 2 x USB 2.0 connec M Key, type 2242/2260/2280 storage devices support (SATA & PCIE 4.0 x 4 mode) - 1 x M.2 Socket (SATA & PCIE 3.0 x 4 mode) - 1 x SPI TPM header - 4 x SATA 6Gb/s connector(s) - 1 x 24-pin EATX P panel audio connector(s) (AAFP) - 1 x Clear CMOS jumper(s) - 1 x System panel connector - 1 x COM

BIOS:	- 256 Mb Flash ROM, UEFI AMI BIOS
Ostalo:	ASUS TUF PROTECTION - ASUS DIGI+ VRM (Digital power design with Dr. MOS) - ASUS Enhanced DR ASUS Overvoltage Protection - ASUS SafeSlot - ASUS Stainless-Steel Back I/O ASUS Q-Design - ASUS Device [yellow green]) - ASUS Q-Slot ASUS Thermal Solution - Aluminum M.2 heatsink ASUS EZ DIY Standard RGB headers - Addressable Gen 2 RGB header