

**Mechanical control Toaster, ( ATS0003 )**

Šifra: 47871

Kategorija proizvoda: Grilovi i tosteri

Proizvođač: Aeno

**Cena: 5.163,00** rsd.

|                                            |                                                                                                                      |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Kitchen Appliance Type:                    | Toaster                                                                                                              |
| Control Type:                              | Mechanical                                                                                                           |
| Chassis Material:                          | Plastic<br>Stainless Steel                                                                                           |
| Cooking Programs Quantity:                 | 4 Automatic Programs                                                                                                 |
| Automatic Cooking Programs:                | Defrost<br>Cancel<br>Reheat<br>Toast                                                                                 |
| Additional Features:                       | LED Indication<br>7 Browning Levels<br>Anti-Slip Feet<br>6 Preset Types of Bread<br>High Lift<br>Anti-Jam Protection |
| Quantity of Removable Trays:               | 1                                                                                                                    |
| Set Includes:                              | Crumb Tray                                                                                                           |
| External Color:                            | Brushed Stainless Steel                                                                                              |
| Cord Length (m):                           | 0.75 m                                                                                                               |
| Certifications:                            | CE, EMC, REACH, ROHS and LFGB                                                                                        |
| Depth (mm):                                | 265 mm                                                                                                               |
| Height (mm):                               | 155 mm                                                                                                               |
| Width (mm):                                | 180 mm                                                                                                               |
| Input Voltage:                             | AC 220-240 V                                                                                                         |
| Input Frequency:                           | 50/60 Hz                                                                                                             |
| Nominal Output Power:                      | 800 W                                                                                                                |
| Maximum Output Power:                      | 950 W                                                                                                                |
| Maximum Operating Ambient Temperature:     | 45 °C                                                                                                                |
| Minimum Operating Ambient Temperature:     | 10 °C                                                                                                                |
| Maximum Non-Operating Ambient Temperature: | 45 °C                                                                                                                |
| Minimum Non-Operating Ambient Temperature: | 10 °C                                                                                                                |
| Maximum Operating Humidity:                | 95 %                                                                                                                 |
| Minimum Operating Humidity:                | 10 %                                                                                                                 |
| Maximum Non-Operating Humidity:            | 75 %                                                                                                                 |
| Minimum Non-Operating                      |                                                                                                                      |

|                               |               |
|-------------------------------|---------------|
| Humidity:                     | 25 %          |
| Warranty Products Returnable: | Yes           |
| Warranty Term (month):        | 24 month(s)   |
| Warranty validation Criteria: | Serial Number |
| Pack Length (mm):             | 303 mm        |