

EDGECORE 24 ports 101001000Base-T + 4G SFP  
uplink ports with 24 port PoE (200W) ( ECS2100-  
28P )

Šifra: 51361  
Kategorija proizvoda: Switch  
Proizvođač: Edgecore



Cena: **48.159,00** rsd.

|                                 |                                                                                                                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Flash Memory:                   | 32 MB                                                                                                                                                                                                                  |
| RAM:                            | 256 MB                                                                                                                                                                                                                 |
| Number of Ports:                | 24 x 10Base-T100Base-TX1000Base-T (Gigabit EthernetFast EthernetEthernet) 4 x (Gigabit Ethernet)                                                                                                                       |
| Switching Layers:               | Layer 2<br>Layer 3<br>Layer 4                                                                                                                                                                                          |
| MAC Address Table Size:         | 8K                                                                                                                                                                                                                     |
| NetworkTransport Protocol:      | IPv4<br>HTTP<br>IPv6<br>DHCP<br>SNTP<br>NTP<br>DNS<br>HTTPS<br>SNMPv1<br>SNMPv2c<br>SNMPv3<br>IGMP<br>Telnet<br>IGMPv2<br>SSL<br>RMON<br>STP<br>RSTP<br>MSTP<br>IGMPv3<br>SSH<br>LLDP                                  |
| Networking Compliant Standards: | IEEE 802.1D(Spanning Tree Protocol)<br>IEEE 802.1p(QoS)<br>IEEE 802.1Q(VLAN)<br>IEEE 802.1X<br>IEEE 802.3<br>IEEE 802.3ab<br>IEEE 802.3ad<br>IEEE 802.3af<br>IEEE 802.3u<br>IEEE 802.1s<br>IEEE 802.1w<br>IEEE 802.3az |

IEEE 802.3at  
IEEE 802.1ax

|                                        |                                                                              |
|----------------------------------------|------------------------------------------------------------------------------|
| Networking Features:                   | Jumbo Frames Support<br>Web Interface<br>Access Control List<br>24 Ports PoE |
| Device Location:                       | Plug-in Module                                                               |
| Mounting Capability:                   | Rackmount                                                                    |
| Standard Rack Height:                  | 1U                                                                           |
| LAN:                                   | 24 (RJ-45)                                                                   |
| SFP:                                   | 4                                                                            |
| Serial:                                | 1 (RJ-45)                                                                    |
| Power over EthernetPower Adapter:      | AC 100-240 V, 50/60 Hz                                                       |
| Power Consumption Operational:         | 200 W                                                                        |
| Depth (mm):                            | 440 mm                                                                       |
| Height (mm):                           | 44 mm                                                                        |
| Width (mm):                            | 220 mm                                                                       |
| Nominal Weight:                        | 2.8 kg                                                                       |
| External Color:                        | Black                                                                        |
| Maximum Operating Ambient Temperature: | 50 °C                                                                        |
| Maximum Operating Humidity:            | 90 %                                                                         |
| Minimum Operating Ambient Temperature: | 0 °C                                                                         |
| Minimum Operating Humidity:            | 10 %                                                                         |
| Mean Time Between Failures:            | 681017 hr                                                                    |
| Warranty Products Returnable:          | Yes                                                                          |
| Warranty Term (month):                 | 36 month(s)                                                                  |
| Warranty validation Criteria:          | Serial Number                                                                |
| Pack Weight Brutto (kg):               | 4 kg                                                                         |