

MB s1700 ASRock Z790 PG LIGHTNING 90-MXBKA0-A0UAYZ

Šifra: 8223

Kategorija proizvoda: Intel

Proizvođač: AsRock

Cena: **18.210,00** rsd.

CPU

- Supports 13th Gen & 12th Gen Intel® Core™ Processors (LGA1700)
- Supports Intel® Hybrid Technology
- Supports Intel® Turbo Boost Max 3.0 Technology
- Supports Intel® Thermal Velocity Boost (TVB)
- Supports Intel® Adaptive Boost Technology (ABT)

Chipset

- Intel® Z790

BIOS

- 128Mb AMI UEFI Legal BIOS with GUI support

Audio

- 7.1 CH HD Audio (Realtek ALC897 Audio Codec)
- Nahimic Audio

Slots

CPU:

- 1 x PCIe 5.0 x16 Slot (PCIE1), supports x16 mode*

Chipset:

- 1 x PCIe 4.0 x16 Slot (PCIE4), supports x4 mode*
- 3 x PCIe 3.0 x1 Slots (PCIE2, PCIE3 and PCIE5)*
- 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT



Memory

- Dual Channel
- 4 x DDR5 Slots
- Supports Intel® Optane™
- 7200+ MHz
- Max. 128GB
- Supports Intel® Optane™

Graphics

- *1 DP
- 1 DP
- 1 x eDP
- 2 DP
- 60Hz
- 2 DP
- 1 x HDMI
- and more

***Intel®**

- outputs
- are GPU

LAN

- 2.5 GbE
- Dragon
- Support
- Smart
- Visual
- Visual
- Optim
- Stream
- User

PCIe WiFi module and Intel® CNVio/CNVio2 (Integrated WiFi/BT)

- Supports AMD CrossFire™

*Supports NVMe SSD as boot disks

Storage

CPU:

- 1 x Hyper M.2 Socket (M2_1, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

Chipset:

- 1 x Hyper M.2 Socket (M2_2, Key M), supports type 2242/2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

- 1 x Hyper M.2 Socket (M2_3, Key M), supports type 2260/2280 SATA3 6.0 Gb/s & PCIe Gen4x4 (64 Gb/s) modes*

- 1 x Hyper M.2 Socket (M2_4, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

- 4 x SATA3 6.0 Gb/s Connectors

*Supports Intel® Volume Management Device (VMD)
Supports NVMe SSD as boot disks

USB

- 1 x USB 3.2 Gen2x2 Type-C (Rear)

- 1 x USB 3.2 Gen2 Type-A (Rear)

- 1 x USB 3.2 Gen1 Type-C (Front)

- 9 x USB 3.2 Gen1 Type-A (5 Rear, 4 Front)

- 3 x USB 2.0 (1 Rear, 2 Front)

*All USB ports support ESD Protection

Rear Panel I/O

- 2 x Antenna Mounting Points

- 1 x PS/2 Mouse/Keyboard Port

- 1 x HDMI Port

- 1 x USB 3.2 Gen2 Type-A Port (10 Gb/s)

- 1 x USB 3.2 Gen2x2 Type-C Port (20 Gb/s)

- 5 x USB 3.2 Gen1 Ports

- 1 x USB 2.0 Port

- 1 x RJ-45 LAN Port

- HD Audio Jacks: Line in / Front Speaker / Microphone

RAID

- Support

storage

- Support

storage

Connect

- 1 x eL

- 1 x SP

- 1 x PC

- 1 x R

- 3 x A

- 1 x C

- 1 x C

Speake

Softw

5ftw

(SRD)

- ASR2

- ASR8

Defi

- ASR6

- ASR6

ASR6

- ASR6

- ASR6

ASR6

- 1 x Fr

*Suppo

**Supp

***CPU

**** CP

(24W).

****C

(24W).

CPU_FA

3-pin o

Form Factor

- ATX F

